BUTYL ACRYLATE

CAS Number: 141-32-2

Other Names: n-Butyl acrylate, butyl prop-2-enoate, Acrylic acid butyl ester.



Formula: C₇H₁₂O₂

PRODUCT INTRODUCTION

Butyl acrylate is an acrylate ester obtained by the formal condensation of the hydroxy group of butan-1ol with the carboxy group of acrylic acid. Butyl acrylate appears as a clear colorless liquid with a sharp characteristic odor. Very slightly soluble in water and somewhat less dense than water. Used for making paints, coatings, caulks, sealants, adhesives.

PHYSICAL AND CHEMICAL PROPERTIES

Purity	99.73 wt%
Color	5 APHA
Water	0.01 wt%
Inhibitor (MEHQ)	100 wt ppm
Acidity	6 wt ppm
Specific Gravity (20/4°C)	0.9

APPLICATIONS

- Butyl acetate is used as monomer for the manufacture of polymers and resins for textile and leather finishes and paint formulations.
- Butyl acrylate is used in the production of homopolymers and co-polymers such as acrylic acid and its salts, esters, amides, methacrylates, acrylonitrile, maleates, vinyl acetate, vinyl chloride, vinylidene chloride, styrene, butadiene and unsaturated polyesters.
- When used in latex paint formulations acrylic polymers have good water resistance, low temperature flexibility and excellent weathering and sunlight resistance.

PACKAGING OPTIONS

Drums